

6x2 Hybrid Multiplexer

HMX-62N

6x2 Hybrid Multiplexer combines the existing commercial (low & mid.) bands and CBRS/C-Bands. It includes a hybrid combiner and two triplexers internally.

- Hybrid Multiplexer with 6 Inputs & 2 Outputs
- Applicable to signal combining for low and mid. band DAS remotes
- Signal combining expansion to CBRS/C-Band
- Wall-Mountable
- Low PIM Rated
- IP67 Outdoor Rated
- High Reliability, RoHS compliant



Parameters		Specifications					
Model		HMX-62N					
Input Port No.		1	6	2	5	3	4
Freq. Range [MHz]		617-894		1710-2690		3450 - 4200	
Insertion Loss [dB]		3.4±1.2		3.5±1.0		3.5±1.2	
Return Loss [dB]		18					
Port Isolation [dB]	@ Same Band	25				21	
	@ Cross Band	45					
Power Handling [W]		150					
PIM [dBc]		-161					
IP Rating		IP67					
RF Connectors		4.3-10 Female					
Size (W x H x D)		14.4" x 6.9" x 1.7"					
Weight [lb]		15					

* Specifications are subject to change without prior notification.

Rev.2

6x2 Hybrid Multiplexer HMX-62N

Mechanical Drawing

