

# 19" 1U Low PIM Attenuator Tray

LPA-XX-60-R

19" 1U Rackmount, 600-6000MHz Broadband Low PIM Rated 10dB, 20dB, 30dB Fixed Attenuator Trays. These can be used for Radio, Small Cell and DAS Signal Attenuation.

- 19" 1RU Rack Mountable Low PIM Fixed Attenuator
- 50W Rated Low PIM 4x 10dB (or 20dB, 30dB) Attenuator Tray
- Best fit with LPPOI (Low Power POI) for feeding high power signal to DAS
- Signal padding for 5W rated AFT-POI RIU (Radio Interface Unit)
- Wideband Range, 600-6000 MHz
- Convenient Size for easy installation
- Indoor Application



Parameter	Specifications		
Model	LPA-10-60-R	LPA-20-60-R	LPA-30-60-R
Freq. Range [MHz]	600 - 6000		
No. of Low PIM Attenuator [dB]	4		
Attenuation [dB]	10	20	30
Attenuation Accuracy [dB]	± 1.5	± 1.7	± 1.8
VSWR	≤ 1.35 @600-2700MHz, ≤ 1.4 @2700-6000MHz		
PIM [dBc]	-161		
Power Rating [W]	50 (Avg.) per each Attenuator		
Operating Temp. [°F]	-20 to +149		
RF Connector	4.3-10 Female		
Size (W x H x D)	18.97" x 1.72" x 13.78"		
Weight [lb]	15		

\* Specifications are subject to change without prior notification.

Rev.0

