

3550-3670 & 3700-4200MHz Diplexer for CBRS/C-Band

SDXS-36-CB / SDXT-36-CB

SDXS/T-36-CB is a RF Diplexer which combines CBRS (3350-3670MHz) with C-Band (3700-4200MHz) utilized for multi-band DAS.

- Easy integration of CBRS / C-Band combining for multi-band DAS
- Low Insertion / High Port Isolation
- Low PIM Rated
- Outdoor IP67 & Salt Fog Rated
- Goretex Plug and Ground Terminal
- Wall/Pole Mountable Diplexer
- Single & Twin Configuration
- Compact Size for Easy Installation



Parameter		Specifications	
Model	Single	SDXS-36-CB	
	Twin	SDXT-36-CB	
Freq. Range [MHz]		CBRS (3550-3670)	C-Band (3700-4200)
Insertion Loss [dB]		0.9	
Return Loss [dB]		18	
Port Isolation [dB]		50	
Power Rating [W]		150 Avg. per port	
PIM [dBc]		-161	
IP Rating		IP67, 30-day Salt Fog IAW ASTM-B117	
Protection		Goretex Vent Plug & Ground Terminal (6 AWG)	
Operating Temp. [°F]		-40 to +149	
RF Connector		4.3-10 Female	
Size (W x H x D)		Single: 5.71" x 7.43" x 1.46", Twin: 5.71" x 7.43" x 3.19"	
Weight [lb]		Single: 3.7, Twin: 7.2	

* Specifications are subject to change without prior notification.


Rev.1

3550-3670 & 3700-4200MHz Diplexer for CBRs/C-Band


SDXS-35-CB / SDXT-35-CB

Mechanical Drawing

SDXS-36-CB



SDXT-36-CB



Inch [mm]